



**Samsung Videowall Products**

**KT-LS40LNKX**

**KT-LS46LNKX**

PANEL	Screen Size(diagonal)	40inch TFT	46inch TFT	
	Aspect ratio/Displayable Colors	1366 X 768	16:9 / 16.7M (8bits-true)	
	Resolution	1920 x 1080 (Full HD)	1920 x 1080 (Full HD)	
	MAX. Brightness	700cd/m2 (Typical)	700cd/m2 (Typical)	
	Contrast Ratio(Typ)	3000:1	4000:1	
	Response Time/View Angle	8/89	8/89	
Features	Video signal (in)	PC(1EA),DVI(1EA),CVBS(1EA),COMPONENT(1EA),S-VIDEO(1EA)		
	Video signal (out)	PC(1EA),DVI(1EA),CVBS(1EA),COMPONENT(1EA),S-VIDEO(1EA)		
	Sound (in)	-		
	Sound (out)	-		
	OSD Control	Remote control IR & behind button		
	ISP	RS-232		
	Multi Control	MWCP(software), IR_KEY BOARD		
	Input Resolution	Display Clock : Max 165MHz , 640x480 (60Hz) ~ 1920x1080 (60Hz)		
	Power Management	Without DPMS		
	Operating Temperature	0~40℃ / 20~90%		
	Storage Temperature	-20~65℃ / 5~90%		
General	Bezel width (mm)	886.7*499.2	1022.4*575.6	
	Wall mount size (mm)	638*380(M8 TAP)		
	Set Dimen. (mm)	Length	914.7	1050.4
		Width	527.2	603.6
		Depth	105.8	105.8
	Weight(kg)	22	26.1	
	Packing Dimen. (mm)	Length	1130	1260
		Width	300	300
		Depth	720	795
	Volumetric Weight(kg)	30	36.5	
	Power Supply	100~240V, (50 / 60Hz)		
	Power Consumption	230W	280W	

